

## Advantages

- Dispenser-based disabling prevents the entire site from shutting down in the event of an EVR failure.
- Wireless Flow Meter and Pressure Sensor interface option when conduit is not present.
- Ethernet-ready, web-based remote access provides the user with remote access to VRM status information, reports and alarm information using any web browser.
- Create custom rules to send e-mails and text messages on alarms and events directly from the console to service and compliance personnel.
- User-friendly touch screen interface with icon-based navigation.
- Scalable open architecture for easy and cost-saving future upgrades.

## Wireless™ TS-DTU

- Uses dispenser power wires to transmit data
- Multi-industry proven power line communications technology.
- Save weeks of installation time.
- Save thousands of dollars in costly conduit installation and avoid damaged and blocked conduit.
- Reduces the cost of the console
- No disruption of forecourt by having to break concrete.
- No need to pull wires.
- Will not interfere with dispenser operation.
- UL approved for installation in most common dispenser models.
- Works even if some dispensers are on different phases.

## In-Station Diagnostics (ISD)

### Now Available with the Wireless™ Option

The INCON vapor recovery monitoring (VRM) option meets or exceeds all ISD requirements for ensuring that all components of the vapor recovery system are functioning normally. Recorded sales transactions are compared to data obtained from a TS-VFM vapor flow meter installed in each dispenser to verify that equivalent vapors are recovered from the vehicle when fuel is dispensed. The pressure of the vapor containment space is constantly monitored by the TS-VPS vapor pressure sensor and tested for over pressure and leakage conditions. Local and remote notification options alert the user of abnormalities and dispenser-based disabling keeps the rest of the site up and running when a single dispenser EVR system has a problem. The Wireless option featuring the TS-DTU eliminates the need to break concrete to install new conduit or even pull wires. It also reduces the cost of the console by removing the need for certain modules.



TS-5000



TS-550



TS-EMS



Vapor Flow Meter



Vapor Pressure Sensor



Data Transfer Unit

Part Number	Description
TS-VFM	Vapor flow meter, one per dispenser
TS-VPS	Vapor pressure sensor, one per site
TS-VRM	Vapor recovery monitoring software
TS-DTU/P	Data transfer unit for Wireless VFM and VPS communications
TS-DRK	Dispenser retrofit install kit for TS-DTU/P

- Notes: 1. Approved by California Air Resources Board EO VR-202.  
 2. Minimum module requirements include one TS-PRB, TS-ACI, TS-420IB, TS-RLY or TS-10ARLY.  
 3. TS-VRM software is included in the TS-EMS console.  
 4. Order one TS-DTU/P and one TS-DRK install kit per dispenser. Order one additional TS-DTU/P for the console. Control Module software 9.5 or greater required.  
 5. TS-EMS consoles using the Wireless option do not require the TS-PRB or TS-420IB modules.