

Service Station Hardware

Model 615, 635 and 670 Angle Check Valves




Angle Check Valves are used on suction system fuel lines to maintain prime. EBW's Angle Check valves are installed at the top of an underground storage tank suction line. Single poppet models are typically used where access to the valve is readily available.

MATERIALS
Body: Zinc-plated cast iron
Seat: Brass
Poppet: Brass
NPT: Brass
Spring: Stainless steel



SINGLE POPPET



PART	A		B		C		D		E	
	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.
615-301-01	1.5	38.1	2.19	55.6	1.82	46.2	2.62	66.5	44.4	112.8
635-201-01	1.81	45.9	2.69	68.3	2.43	61.7	2.66	67.6	5.09	129.3
635-210-01*	1.81	45.9	2.69	68.3	2.43	61.7	2.66	67.6	5.09	129.3
670-300-01	2.47	62.7	3.65	92.7	2.30	58.4	3.75	95.2	6.05	153.7

PART	SIZE (NPT)		POPPET TYPE	WEIGHT	
	IN.	MM.		LBS.	KG.
615-301-01	1.5	38	Single	3.8	1.7
635-201-01	2.0	51	Single	7.25	3.3
635-210-01*	2.0	51	Single	7.25	3.3
670-300-01	2.0	51	Double	12.5	5.7

*Spring loaded

